

Catálogo de Especificaciones Técnicas: Terminales Eléctricas de Ojillo para Alta Temperatura (Serie OT)

Propiedad de Heatecx Limited | www.heatecx.com

ITEM NO.	d2 (mm)	W (mm)	L (mm)	H (mm)	d1 (mm)	D (mm)	T (mm)	PCS/PACK
OT0.5-3	3.2	6	13	4	2.2	1.2	0.5	1000
OT0.5-4	4.2	7	14	4	2.2	1.2	0.5	1000
OT1-3	3.2	6	14.4	5	3.2	1.7	0.7	1000
OT1-4	4.3	7.6	16.8	5	3.2	1.7	0.7	1000
OT1-5	5.3	9.7	19.3	5	3.2	1.7	0.7	1000
OT1-6	6.5	11.4	21.8	5	3.2	1.7	0.7	1000
OT1.5-3	3.2	6	14.4	5	3.8	2.0	0.7	1000
OT1.5-4	4.3	7.8	16.8	5	3.8	2.0	0.7	1000
OT1.5-5	5.3	9.6	19.3	5	3.8	2.0	0.7	1000
OT1.5-6	6.5	11.5	21.5	5	3.8	2.0	0.7	1000
OT1.5-10	10.5	15	29	5	3.8	2.0	0.7	1000
OT1.5-12	12.5	18	29	5	3.8	2.0	0.7	1000
OT1.5-16	16.5	24	34	5	3.8	2.0	0.7	1000
OT2.5-3	3.2	6.5	15	5	4.2	2.6	0.7	1000
OT2.5-4	4.3	7.6	17	5	4.2	2.6	0.7	1000
OT2.5-5	5.3	9.5	19.3	5	4.2	2.6	0.7	1000
OT2.5-6	6.5	11	21.4	5	4.2	2.6	0.7	1000
OT2.5-8	8.5	15	25	5	4.2	2.6	0.7	1000

OT2.5-10	10.5	18	29	5	4.2	2.6	0.7	1000
OT2.5-12	12.5	19	29	5	4.2	2.6	0.7	1000
OT2.5-16	16.5	24	34	5	4.2	2.6	0.7	1000
OT4-4	4.3	8.5	18.1	6	5.2	3.2	1.0	1000
OT4-5	5.3	10	20.5	6	5.2	3.2	1.0	1000
OT4-6	6.5	12	23.2	6	5.2	3.2	1.0	1000
OT4-8	8.5	15	26.5	6	5.2	3.2	1.0	1000
OT4-10	10.5	18	31.2	6	5.2	3.2	1.0	1000
OT4-12	12.5	19.8	33.2	6	5.2	3.2	1.0	1000
OT6-4	4.3	9	19.5	7	6.2	4.2	1.0	1000
OT6-5	5.3	11	23	7	6.2	4.2	1.0	1000
OT6-6	6.5	12	24.5	7	6.2	4.2	1.0	1000
OT6-8	8.5	15	27.5	7	6.2	4.2	1.0	1000
OT6-10	10.5	18.2	32.3	7	6.2	4.2	1.0	1000
OT6-12	12.5	20	34	7	6.2	4.2	1.0	1000
OT10-4	4.3	10	23.2	8.5	5.6	8	1.2	1000
OT10-5	5.3	12	28	8.5	5.6	8	1.2	1000
OT10-6	6.5	14	27.5	8.5	5.6	8	1.2	1000
OT10-8	8.5	16	30.2	8.5	5.6	8	1.2	1000
OT10-10	10.5	17.3	34.3	8.5	5.6	8	1.2	1000
OT10-12	12.5	21	38.2	8.5	5.6	8	1.2	1000
OT16-6	6.3	14.5	32.5	10.5	7	10	1.5	500
OT16-8	8.8	16	33.5	10.5	7	10	1.5	500
OT16-10	10.5	20.5	38	10.5	7	10	1.5	500

OT16-12	12.5	23	41.5	10.5	7	10	1.5	500
OT16-14	14.5	30	54	14	7	10	1.5	500
OT16-16	16.5	30	54	14	7	10	1.5	500
OT25-6	6.3	17	33.5	14	8.5	12	1.8	200
OT25-8	8.5	21	37.5	14	8.5	12	1.8	200
OT25-10	10.5	23	43	14	8.5	12	1.8	200
OT25-12	12.5	24	45	14	8.5	12	1.8	200
OT25-14	14.5	26	47	14	8.5	12	1.8	200
OT25-16	16.5	30	54	14	8.5	12	1.8	200
OT35-6	6.3	17	38	14	9.5	13.1	1.8	200
OT35-8	8.5	21	37.5	14	9.5	13.1	1.8	200
OT35-10	10.5	23	43	14	9.5	13.1	1.8	200
OT35-12	12.5	25	47	14	9.5	13.1	1.8	200
OT35-14	14.9	27	50	14	9.5	13.1	1.8	200
OT35-16	16.5	30	54	14	9.5	13.1	1.8	200
OT50-6	6.3	22	39	14	11.5	15.1	1.8	200
OT50-8	8.5	22	39	14	11.5	15.1	1.8	200
OT50-10	10.5	24.5	43.5	14	11.5	15.1	1.8	200
OT50-12	12.5	26	47.5	14	11.5	15.1	1.8	200
OT50-14	14.5	30	54	14	11.5	15.1	1.8	200
OT50-16	16.5	30	54	14	11.5	15.1	1.8	200
OT70-6	6.3	22	49	18.5	13.1	17.5	2.2	200
OT70-8	8.5	22	49	18.5	13.1	17.5	2.2	200
OT70-10	10.5	24.5	51	18.5	13.1	17.5	2.2	200
OT70-12	12.5	24.5	51	18.5	13.1	17.5	2.2	200
OT70-14	14.5	29	60	18.5	13.1	17.5	2.2	200

OT70-16	16.5	29	60	18.5	13.1	17.5	2.2	200
OT95-8	8.5	23	51	20	15.1	19.5	2.2	100
OT95-10	10.5	27	53	20	15.1	19.5	2.2	100
OT95-12	12.5	27	53	20	15.1	19.5	2.2	100
OT95-14	14.5	29	65	20	15.1	19.5	2.2	100
OT95-16	16.5	29	65	20	15.1	19.5	2.2	100
OT120-8	8.5	30	30	22	17	22.2	2.6	100
OT120-10	10.5	30	30	22	17	22.2	2.6	100
OT120-12	12.5	30	30	22	17	22.2	2.6	100
OT120-14	14.5	30	30	22	17	22.2	2.6	100
OT120-16	16.5	30	30	22	17	22.2	2.6	100
OT150-8	8.5	31	31	25.5	18.1	24.5	3.2	50
OT150-10	10.5	31	31	25.5	18.1	24.5	3.2	50
OT150-12	12.5	31	31	25.5	18.1	24.5	3.2	50
OT150-14	14.5	31	31	25.5	18.1	24.5	3.2	50
OT150-16	16.5	31	31	25.5	18.1	24.5	3.2	50
OT185-8	8.5	32	67	27	20	27.2	3.5	50
OT185-10	10.5	32	67	27	20	27.2	3.5	50
OT185-12	12.5	32	67	27	20	27.2	3.5	50
OT185-14	14.5	32	67	27	20	27.2	3.5	50

OT185-16	16.5	32	67	27	20	27.2	3.5	50
OT240-8	8.5	38	70	30	24	32	4.0	50
OT240-10	10.5	38	70	30	24	32	4.0	50
OT240-12	12.5	38	70	30	24	32	4.0	50
OT240-14	14.5	38	70	30	24	32	4.0	50
OT240-16	16.5	38	70	30	24	32	4.0	50
OT300-10	10.5	50.5	103	35	29	37.5	4.2	50
OT300-12	12.5	50.5	103	35	29	37.5	4.2	50
OT300-14	14.5	50.5	103	35	29	37.5	4.2	50
OT300-16	16.5	50.5	103	35	29	37.5	4.2	50
OT300-18	18.5	50.5	103	35	29	37.5	4.2	50
OT300-20	21.5	50.5	103	35	29	37.5	4.2	50